



IC-M37

VHF MARINE TRANSCEIVER

6 Watt VHF with Float'n Flash and 12 Hours of Operation

**Large Keys and
Easy-to-Grip Design**

6 W RF Output Power

700 mW Audio Output

**More than 12 Hours* of
Long-Lasting Operating Time**
(with BP-296)

* TX: RX: Standby = 5 : 5 : 90.

Channel History Function
Stores the Last Five Channels
Used for Easy Recall

Float'n Flash Function

The radio floats with a flashing LED light to help you retrieve it from the water.



Float'n Flash function (front/back)



Read this QR code
to watch a movie!

Made
in
JAPAN

AND MORE

- IP57 dust-protection and waterproof protection (1 m depth of water for 30 minutes)
- Low Battery Alert function
- Voice Loud and Mute function enables to temporary maximize/mute the volume
- AquaQuake™ function prevents audio degradation from a water-logged speaker
- Dualwatch and Tri-Watch functions
- Favorite Channel function
- Instant access to channel 16 and the Call channel
- BP-296 user replaceable Li-ion battery pack supplied
- Weather channels with Weather Alert function

OPTIONS

Some options may not be available in some countries. Please ask your dealer for details.

BATTERY PACK



BP-296
Rechargeable Li-ion 3.6 V
2350 mAh (typ.), 2200 mAh (min.).

BATTERY CASE



BP-297*1
For AAA (LR03)×3 alkaline cells.
Output power: 1 W.

BATTERY CHARGER



BC-235
Desktop charger. Same as supplied.

AC ADAPTER



BC-217SA/SE*2
Use with BC-235. Same as supplied.

SPEAKER-MICROPHONE



HM-213
IP57 dust-protection and waterproof protection. Floats in water with the radio.

BELT CLIP



MB-133
Same as supplied.

ANTENNA

FA-SC59V
Same as supplied.



The "3D GENUINE Icom label" is attached to the rear chassis under the battery. (Remove the battery pack)
Check the Icom website for details:
<http://www.icom.co.jp/world/genuine-info/>

SPECIFICATIONS

GENERAL		
Frequency range	TX RX	156.025–157.425 MHz 156.050–163.275 MHz
Usable channel groups	INT, USA, CAN, WX channels	
Type of emission	16K0G3E	
Current drain (at 3.7 V DC)	TX (6.0 W/1.0 W output) RX (Max. audio. Int. SP/Ext. SP)	2.75 A/1.0 A 0.4 A/0.2 A
Operating temperature range	–20°C to +60°C, –4°F to +140°F	
Antenna impedance	50 Ω	
Dimensions (W×H×D) (projections not included)	59.7 × 140.5 × 38.7 mm, 2.4 × 5.5 × 1.5 in	
Weight (approximate)	293 g, 10.3 oz (with BP-296, antenna and belt clip)	
TRANSMITTER		
Output power (High/Low)	6 W/1 W	
Max. frequency deviation	±5 kHz	
Frequency stability	±10 ppm	
Spurious emissions	–68 dBc typical	
RECEIVER		
Sensitivity (at 12 dB SINAD)	0.25 μV typical	
Squelch sensitivity (Threshold)	0.25 μV typical	
Adjacent channel selectivity	70 dB typical	
Spurious response	70 dB typical	
Intermodulation	70 dB typical	
Hum and noise	40 dB	
Audio output power (at 10% distortion)	Internal SP	0.7 W typical (8 Ω load)
	External SP	0.3 W typical (4 Ω load)

Measurements made in accordance with TIA/EIA-603.
All stated specifications are subject to change without notice or obligation.

Applicable U.S. Military Specifications & IP Rating

Standard	MIL-810 G	
	Method	Procedure
Low Pressure	500.5	I, II
High Temperature	501.5	I, II
Low Temperature	502.5	I, II
Temperature Shock	503.5	I-C
Solar Radiation	505.5	I
Rain Blowing/Drip	506.5	I, III
Humidity	507.5	II
Salt Fog	509.5	–
Dust Blowing	510.5	I
Immersion	512.5	I
Vibration	514.6	I
Shock	516.6	I, IV

Also meets equivalent MIL-STD-810-C, -D, -E and -F.

Ingress Protection Standards

Water	IP57 dust protection and waterproof protection (1 m depth of water for 30 minutes)
-------	---

Supplied accessories:

- BP-296 battery pack
- BC-235 desktop charger
- BC-217SA/SE* AC adapter
- FA-SC59V antenna
- MB-133 belt clip
- Hand strap

* May differ or not supplied, depending on the transceiver version.

Icom, Icom Inc. and Icom logo are registered trademarks of Icom Incorporated (Japan) in Japan, the United States, the United Kingdom, Germany, France, Spain, Russia, Australia, New Zealand and/or other countries. AQUAQUAKE is a trademark of Icom Incorporated. QR Code is registered trademark of DENSO WAVE INCORPORATED in Japan and in other countries. All other products or brands are registered trademarks or trademarks of their respective holders.

Icom Inc.

1-1-32, Kamiminami, Hirano-Ku, Osaka 547-0003, Japan Phone: +81 (06) 6793 5302 Fax: +81 (06) 6793 0013

www.icom.co.jp/world

Count on us!

Icom America Inc.
www.icomamerica.com

Icom (Europe) GmbH
www.icomeurope.com

Icom (Australia) Pty. Ltd.
www.icom.net.au

Your local distributor/dealer:

Icom Canada
www.icomcanada.com

Icom Spain S.L.
www.icomspain.com

Icom Brazil
E-mail: sales@icombrasil.com

Icom (UK) Ltd.
www.icomuk.co.uk

Icom France s.a.s.
www.icom-france.com